

# ECO LUXXUS 160



Ideal for  
**A**  
Channel Letters

Optimal Depth  
**2-8**  
inches

Module Consumption  
**0.72**  
Watts

High Brightness  
**70**  
Lumens

Beam Angle  
**160°**

Number of modules  
**2**  
per foot

Waterproof  
**IP67**

Long Life Span  
**50,000**  
Hours

Max. Load  
**70**  
Per 60W  
Power Supply

Great for Shallow Signs!

Recommended Depth (inches)	2**	3	4	5	6	7	8
Distance Between Rows (inches)*	3	4-5	6-7	8	10	8-10	8

\* Measurements tested with acrylic face. May vary with thickness of material.

\*\* 3 modules/foot



Product Code	Color	Lumens / Module	Watts / Module	Modules / Foot	Max. load for 60W 12V 5A, Class 2	Operating Temperature	Warranty	Waterproof Rating
GL-EV5-072WET-160-DL	White 6500K	70	0,72W	2	70	-40° C to 70° C	5 years	IP 67
GL-EV5-072WET-160-CW	White 7200K	70	0,72W	2	70	-40° C to 70° C	5 years	IP 67
GL-EV5-072WET-160-R	Red	10	0,72W	2	70	-40° C to 70° C	5 years	IP 67
GL-EV5-072WET-160-G	Green	36	0,72W	2	70	-40° C to 70° C	5 years	IP 67
GL-EV5-072WET-160-B	Blue	9	0,72W	2	70	-40° C to 70° C	5 years	IP 67

\*Product also available in Orange upon request

